

Linha Diesel - 60Hz



Yanmar

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (lit/h)
							C	L	A		
13	10,4	11,7	9,4	BTD22	16,8	2	1356	850	980	420	3,6
20	16	18	14,4	BTD33	26,5	3	1470	850	980	490	5,6



Perkins

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (lit/h)
							C	L	A		
750	600	680	544	2806C-E18TAG3	896	6	3246	1536	2116	4350	145



MWM - International

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (lit/h)
							C	L	A		
40	32	37	30	D229-3	50	3	1541	726	1421	693	9,4
55	44	50	40	MS3.9	68	4	1637	691	1300	847	12,6
55	44	50	40	D229-4	67	4	1778	726	1400	863	11,6
75	60	68	54	MS3.9T	94	4	1657	952	1467	900	17,8
81	65	78	62	D229-6	99	6	2040	986	1494	1139	17,8
105	84	100	80	4.10T	132	4	2025	986	1506	1020	23,5
110	88	100	80	MS4.1TA	136	4	1907	952	1484	1088	22,7
115	92	105	84	4.10TCA	145	4	1955	986	1296	986	24,5
115	92	106	85	TD229EC-6	137	6	2333	986	1426	1267	25,1
150	120	141	113	6.10T	180	6	2335	986	1672	1571	31,0
180	144	168	134	6.10TCA	215	6	2486	986	1672	1659	34,8



Doosan

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (lit/h)
							C	L	A		
625	500	556	445	P180LE	734	10V	3121	1388	1916	2880	128,2
750	600	676	541	P222LE	882	12V	3310	1400	1817	3540	153,9



Volvo

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (lit/h)
							C	L	A		
500	400	455	364	TAD1242GE	610	6	3102	1340	1783	3175	98,4
564	451	506	405	TAD1640GE	671	6	3222	1340	2110	3350	104,8
642	514	570	456	TAD1641GE	768	6	3222	1340	1950	2925	118,6
687	550	625	500	TAD1642GE	821	6	3373	1340	1950	3314	133,6
757	605	687	550	TWD1643GE	917	6	3290	1396	2160	4350	139,0



MTU

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (lit/h)
							C	L	A		
1000	800	920	736	12V2000G85	1210	12V	4267	1580	2220	6500	199,2
1145	916	1038	830	16V2000G45	1373	16V	4720	1752	2222	8734	221,8
1260	1008	1140	912	16V2000G85	1516	16V	4900	1752	2392	9190	243,6
1500	1200	1360	1088	18V2000G85	1781	18V	5091	2000	2451	9680	284,5



Linha Diesel - 60Hz



Hyundai

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (100% carga)
							C	L	A		
20	16	18	14,4	D4BB-G1	28	4	1442	691	1300	512	5,7



Mercedes-Benz

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Massa (kg)	Consumo comb. (100% carga)
							C	L	A		
130	104	120	96	OM366-A	166	6	2144	986	1406	1175	27,4
156	125	142	114	OM366-LA	194	6	2145	986	1516	1300	31,4
290	232	260	208	OM447-A	320	6	2800	1340	1929	2185	56,7
340	272	310	248	OM447-LA506	410	6	2785	1340	1929	2524	67,6
450	360	405	324	OM447-LA505	545	6	2888	1340	2096	2785	80,5



Scania

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Consumo comb. (100% carga)	
							C	L	A		
305	244	290	232	DC9 65A	428	5	2983	1120	1810	2300	61,4
320	256	300	240	DC9 65A	428	5	2983	1120	1810	2300	63,5
360	288	331	264	DC9 65A	428	5	2860	1120	1680	2350	69,9
450	360	405	324	DC12 60A	552	6	3151	1340	2011	2688	81,4
460	368	434	347	DC12 60A	552	6	3176	1340	2011	2707	87,2
500	400	456	364	DC12 53A	605	6	3295	1340	2011	2707	91,5
575	460	550	440	DC16 46A	771	8 V	3410	1400	1877	3740	115,5
650	520	600	480	DC16 46A	771	8 V	3410	1400	1880	3790	124,3



Mitsubishi

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Consumo comb. (100% carga)	
							C	L	A		
1000	800	875	700	S12A2-PTA	1156	12V	4570	1860	2150	8090	194,2
1275	1020	1165	932	S12H-PTA	1523	12V	4480	1860	2390	10600	244,5
1515	1212	1375	1100	S12R-PTA	1795	12V	5711	2050	2830	11010	285,6
2040	1632	1850	1480	S16R-PTA	2380	16V	5390	2360	2869	12400	373,6
2500	2000	2275	1820	S16R-PTAA2	2923	16V	5970	2395	3265	17190	463,3



Cummins

Intermitente		Continua		Motor			Grupo Gerador				
kVA	kWe	kVA	kWe	Modelo	CV	Nº CIL.	Dimensões (mm)			Consumo comb. (100% carga)	
							C	L	A		
52	42	46	37	4B3.9-G2	69	4	1704	726	1331	735	12,8
81	65	74	60	4BT3.9-G4	100	4	1771	986	1409	1007	18
142	114	131	105	6BT5.9-G6	173	6	2137	986	1466	1106	29
170	136	153	122	6BTA5.9-G3	209	6	2137	986	1446	1215	36
200	160	180	144	6CTA8.3-G1	243	6	2356	986	1550	1766	39,5
230	184	210	168	6CTA8.3-G2	281	6	2441	986	1550	1766	48
260	208	232	186	6CTAA8.3-G	322	6	2521	986	1550	1764	52
305	244	290	232	NT855-G6	441	6	2891	1340	1737	2677	67
320	256	300	240	NT855-G6	441	6	2891	1340	1737	2677	69
360	288	325	260	NT855-G6	441	6	2980	1340	1767	2912	74
380	304	345	276	NTA855-G2	471	6	2986	1340	1833	3098	79
450	360	405	324	NTA855-G3	542	6	2986	1340	1833	3098	87
500	400	456	365	NTA855-G5	605	6	3160	1340	1875	3200	100
625	500	569	455	QXS15-G9	762	6	3608	1475	2080	4250	117,8
750	600	681	545	VTA28-G5	913	12V	3831	1830	2283	7149	154
1000	800	900	720	QST30-G2	1217	12V	4361	1743	2328	7973	197
1250	1000	1125	900	QST30-G4	1510	12V	4361	1980	2547	7973	240
1563	1250	1375	1100	KTA50-G3	1876	16V	5651	2276	2507	11435	310
1941	1553	1600	1280	KTA50-G9	2250	16V	5651	2276	2507	11553	330
2500	2000	2250	1800	QSK60-G6	2964	16V	6251	2789	3175	15875	466



Imagens contidas neste catálogo são meramente ilustrativas. Alterações na linha de produtos poderão ser realizadas sem aviso prévio.